

1203+1602-SMC-BK-WT

SMARTWIRE MC LIGHTING CABLE



CABLE SPECIFICATIONS

DESCRIPTION

- ARMOR-INTERLOCKING GALVANIZED STEEL STRIP
- TYPE THHN, TFN SOLID CONDUCTORS
- PERMITS CONDUCTORS OF CLASS 2 AND CLASS 3 CIRCUITS TO BE PLACED IN A CABLE WITH CONDUCTORS OF ELECTRIC LIGHT, POWER, OR CLASS 1 CIRCUITS
- 12-2 BLACK, WHITE, GREEN, 16-2 PURPLE, GRAY

RACKPACK LENGTH

1,000 FEET

APPROX. WEIGHT

258 PER 1,000 FEET

MATERIAL

STEEL

ARMOR

.62" O.D.

INDUSTRY STANDARDS

- UL LISTED AND LABELED (STANDARD 1569)
- UL 66, 83, 1479, 1581, 2556
- NEC 250.118, 300.22(C), 392, 396, 330, 501, 502, 503, 530, 504, 505, 518, 520, 530, 645, 725
- FEDERAL SPECIFICATION A-A-59544 (FORMERLY J-C-30B)
- MEETS ALL APPLICABLE OSHA AND HUD REQUIREMENTS
- MAY BE SURFACE MOUNTED, FISHED AND/OR EMBEDDED IN PLASTER
- CABLE TRAY RATED, INSTALL PER NEC®
- ENVIRONMENTAL AIR-HANDLING SPACE INSTALLATION PER NEC® 300.22(C)
- MADE IN THE USA FULLY PRE-ASSEMBLED AND INSPECTED