

PART NUMBER CRESCOMP


UL LISTED AND RATED TYPE CL3P OR CMP AMX AXLINK PLENUM COMPOSITE CABLE

PAGE 1

■ 0275/0725 FT ●

SMARTWIRE(TM) PRO A/V

A B C D E 0 1 2 3 4 5 6 7 8 9



CABLE SPECIFICATIONS

DESCRIPTION	ELEMENT 1: 18 AWG 2 CONDUCTOR BARE COPPER; ELEMENT 2: 22 AWG 1 PAIR SHIELDED BARE COPPER; LOW-CAP PLENUM COMPOSITE CABLE UL TYPE CL3P/CMP
CONDUCTOR	ELEMENT 1: 18 AWG 16 STRAND; ELEMENT 2: 22 AWG 7 STRAND; BOTH ELEMENTS: BARE COPPER
INSULATION	ELEMENT 1: LOW-SMOKE PVC 0.011"; ELEMENT 2: FLOUROFOAM 0.020"
COLOR CODE	ELEMENT 1: BLACK/RED; ELEMENT 2: BLUE/WHITE
SHIELD	ELEMENT 1: N/A; ELEMENT 2: ALUMINUM/MYLAR
DRAIN WIRE	ELEMENT 1: N/A; ELEMENT 2: 24 AWG 7 STRAND TINNED COPPER
JACKET MATERIAL	OUTER JACKET: LOW-SMOKE PVC 0.015" NOM.
JACKET COLOR	TEAL JACKET WITH YELLOW STRIPE
MARKING	OUTER JACKET: SMARTWIRE PRO A/V A B C D E 0 1 2 3 4 5 6 7 8 9 18 AWG 2 + 22 AWG 1 PR SHLD DATA (UL) CL3P OR CMP C(UL) US FT-6 75C ROHS
OVERALL DIAMETER	.217" NOM.
CABLE WEIGHT	30 LBS/MFT.
TEMPERATURE RATING	75 C / 300 VOLT
CAPACITANCE	ELEMENT 1: N/A ELEMENT 2: 12.8 PF/FT
IMPEDENCE	ELEMENT 1: N/A ELEMENT 2: 102 OHMS +/- 10%

INDUSTRY STANDARDS

FLAME RATING	APPROVED FOR PLENUM USE WITHOUT CONDUIT PER NFPA 262 FLAME TEST
AGENCIES APPROVALS	UL LISTED TYPE CL3P OR CMP; C(UL), ROHS COMPLIANT, MADE IN THE USA



T 800.379.1191

windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC.
All rights reserved. REVISED 09192023