


# MC-LIGHTING-120

SMARTWIRE MC LIGHTING CABLE



## CABLE SPECIFICATIONS

<b>DESCRIPTION</b>	<ul style="list-style-type: none"><li>• ARMOR-INTERLOCKING ALUMINUM STRIP</li><li>• TYPE THHN, TFN SOLID CONDUCTORS</li><li>• PERMITS CONDUCTORS OF CLASS 2 AND CLASS 3 CIRCUITS TO BE PLACED IN A CABLE WITH CONDUCTORS OF ELECTRIC LIGHT, POWER, OR CLASS 1 CIRCUITS</li><li>• 12-2 BLACK, WHITE, GREEN, 16-2 PURPLE, GRAY</li></ul>
<b>RACKPACK LENGTH</b>	1,000 FEET
<b>APPROX. WEIGHT</b>	148 PER 1,000 FEET
<b>MATERIAL</b>	ALUMINUM
<b>ARMOR</b>	.62" O.D.

## INDUSTRY STANDARDS

- UL LISTED AND LABELED (STANDARD 1569)
- UL 66, 83, 1479, 1581, 2556
- NEC 250.118, 300.22(C), 392, 396, 330, 501, 502, 503, 530, 504, 505, 518, 520, 530, 645, 725
- FEDERAL SPECIFICATION A-A-59544 (FORMERLY J-C-30B)
- MEETS ALL APPLICABLE OSHA AND HUD REQUIREMENTS
- MAY BE SURFACE MOUNTED, FISHED AND/OR EMBEDDED IN PLASTER
- CABLE TRAY RATED, INSTALL PER NEC®
- ENVIRONMENTAL AIR-HANDLING SPACE INSTALLATION PER NEC® 300.22(C)
- MADE IN THE USA FULLY PRE-ASSEMBLED AND INSPECTED