


PART NUMBER RG6QP-WHT

ETL Listed and Rated CMP

■ 0275/0725 FT●

ROOM JACK

A B C D E 0 1 2 3 4 5 6 7 8 9



CABLE SPECIFICATIONS

DESCRIPTION	Type RG 6/U Plenum, 18 AWG Copper Covered Steel Center Conductor with a Quad Shield, Foil/40% Alum Braid/Foil/60% Alum Braid, ETL Listed Type CMP
CONDUCTOR	18 AWG Copper Covered Steel
SHIELD	2 Foil Shields Plus 40% and 60% Aluminum Braids
JACKET	Low-Smoke PVC .016" Nom.
JACKET COLOR	White Jacket
MARKING	ROOM JACK A B C D E 0 1 2 3 4 5 6 7 8 9 RG6 18 AWG CCS QUAD SHIELD 60/40% AL BRAID C(ETL)US CMP FT6 75C SWEEP TO 3GHZ MADE IN USA
OVERALL DIAMETER	.260" Nom.
CABLE WEIGHT	38 Lbs/M
CAPACITANCE	15.5 pF/ft. Nom.
IMPEDANCE	75 Ohms
TEMPERATURE RATING	60 C / 300 Volt

ATTENUATION

DB/100 FT. (NOM.)	@ FREQUENCY MHz
0.38 dB	1 MHz
0.70 dB	10 MHz
1.48 dB	50 MHz
2.01 dB	100 MHz
4.23 dB	400 MHz
5.96 dB	700 MHz
7.45 dB	1000 MHz
9.34 dB	1450 MHz
10.69 dB	1800 MHz
11.54 dB	2200 MHz
13.07 dB	3000 MHz
18.64 dB	6000 MHz

INDUSTRY STANDARDS

FLAME RATING

Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test

AGENCY APPROVALS

Power Limited Circuit Cable, Class 2, Type CMP, ETL C(ETL)



All specifications referenced are nominal measurements unless otherwise noted.