

# SIG-SSKF-1-EA

KEYSTONE STAINLESS STEEL FACEPLATES



## SINGLE-GANG STAINLESS STEEL FACEPLATES

Brushed stainless steel faceplates allow mounting any combination of keystone jacks and multimedia modules. These faceplates allow for flush mounting of jacks and for a clean appearance. Stainless steel faceplates are ideal for use in environments that require greater durability and a sanitary, easy-to-clean solution.



### FEATURES

- SAE-304 equivalent brushed stainless steel
- High-impact thermoplastic, UL94V-0 fire-retardant
- Flush mounting of jacks
- 1-, 2-, 3-, 4-, and 6-port versions
- W: 70 mm (2.75 in), H: 114 mm (4.5 in), screw spacing: 83 mm (3,28)
- Ideal for environments requiring durability and a sanitary, easy-to-clean solution

### CONSTRUCTION

- Plate: stainless steel, JIS SUS 304 (equivalent to EN 1.4301, SAE 304, UNS 30400)
- Mounting posts: high impact thermoplastic, UL94V-0 fire-retardant

### OVERALL DIMENSIONS

- W: 69.9 mm (2.75 in), H: 114.3 mm (4.50 in)

### MOUNTING DIMENSIONS

- Mounting screw holes distance: 83.3 mm (3.28 in)

### KEYSTONE MODULE MOUNTING DIMENSIONS

- Mounting dimensions: standard keystone footprint
- Panel opening: 14.7 mm (0.579 in) × 19.30 mm (0.760 in)

### ENVIRONMENTAL

- Operating temperature: -10 °C to +60 °C (-14 °F to 140 °F)

WCV<sup>®</sup>

PROVIDED BY OUR VALUED PARTNER • **SIGNAMAX**<sup>™</sup>  
CONNECTIVITY SYSTEMS

All specifications referenced are nominal measurements unless otherwise noted.