

TFX-CCP1.00BK

SCISSOR CUT FOR EASY, BLACK (50')



SCISSOR CUT FOR EASY, FRAY RESISTANT INSTALLATION IN SHOP OR FIELD PRODUCT DESCRIPTION

By adjusting the physical characteristics of the polyethylene terephthalate filaments, the engineers at Techflex® have produced a product with the same specifications as our PET with the unique advantage of being able to cut the material with ordinary scissors and still maintain an extraordinarily fray-resistant end.

FLEXO® CLEAN CUT® (CCP) is ideal for field installers and situations where access to a hot knife is impossible. CCP's fray-resistant properties allow for frequent expansion at the cut end without unraveling. When cut with a hot knife, CCP produces a virtually frayless end. Clean Cut® sets the highest standard for uncoated fray resistance sleeving products.



- Resists Fraying when Cut with Scissors
- Increased Braid Density for Fuller Coverage
- High Abrasion Resistance
- Temperature Range -94°F to 257°F
- Melt Temp. 482°F

Nominal Size	Expansion Range		Available Colors	Lbs./100'
	Minimum	Maximum		
1"	3/4"	1-3/16"	Black (BK), and Gray (GY)	1.24
1-1/4"	1"	1-1/2"		1.56
1-1/2"	1-1/4"	2"		1.85
1-3/4"	1-1/2"	2-1/8"		2.30

