

PART NUMBER 001326BR

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable



CABLE SPECIFICATIONS

DESCRIPTION	16 AWG 2 Conductor Bare Copper, Shielded Plenum, UL Listed C(UL)US CMP
CONDUCTOR	16 AWG (19 Strand) Bare Copper
INSULATION	Low-Smoke PVC .008"
COLOR CODE	Black/Red
SHIELD	Aluminum Mylar
DRAIN WIRE	22 AWG (7 Strand) Tinned Copper
JACKET	Low-Smoke PVC .018"
JACKET COLOR	White Jacket with Green Stripe
MARKING	SMARTWIRE DEVICE/ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 16 AWG C(UL)US CMP ROHS MADE IN THE USA
OVERALL DIAMETER	.184" Nom.
CABLE WEIGHT	31 Lbs/Mft.
CAPACITANCE	76 pF/ft Nom.
IMPEDANCE	25 Ohms
TEMPERATURE RATING	0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE · T 800.379.1191 · windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC. All rights reserved.