PART NUMBER 001365

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

■ 0275/0725 FT •

SMARTWIRE(TM)

DEVICE/ZONE

A B C D E 0 1 2 3 4 5 6 7 8 9





CABLE SPECIFICATIONS

DESCRIPTION 16 AWG 2 twisted Conductor Bare Copper, Non-Shielded Plenum, UL Listed C(UL)US CMP

CONDUCTOR 16 (19/29 Bare Copper) INSULATION Low-Smoke PVC .008"

COLOR CODE Black/White

LAY LENGTH 3.5" LHL (approx. 3.4 TPF)

SHIELD N/A **DRAIN WIRE** N/A

> JACKET Low-Smoke PVC .018"

JACKET COLOR White Jacket with Purple Stripe

> SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 16 AWG C(UL)US CMP ROHS MARKING

> > MADE IN THE USA

OVERALL DIAMETER .184" Nom.

> CABLE WEIGHT 26 Lbs/Mft.

CAPACITANCE 34 pF/Ft. Nom.

IMPEDANCE 55 Ohms

TEMPERATURE RATING 0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test **FLAME RATING**

AGENCY APPROVALS NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA







All specifications referenced are nominal measurements unless otherwise noted.