## PART NUMBER 0013670

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

■ 0275/0725 FT ● SMARTV	VIRE(TM) DEVICE/ZONE A B C D E 0 1 2 3 4 5 6 7 8 9
CABLE SPECIFICATIONS DESCRIPTION CONDUCTOR	16 AWG 2 twisted Conductor Bare Copper, Non-Shielded Plenum, UL Listed C(UL)US CMP 16 (19/29 Bare Copper)
INSULATION	Low-Smoke PVC .008"
COLOR CODE	Black/White
LAY LENGTH	3.5" LHL (approx. 3.4 TPF)
SHIELD	N/A
DRAIN WIRE	N/A
JACKET	Low-Smoke PVC .018"
JACKET COLOR	Brown Jacket
MARKING	SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 16 AWG C(UL)US CMP ROHS MADE IN THE USA
OVERALL DIAMETER	.184" Nom.
CABLE WEIGHT	26 Lbs/Mft.
CAPACITANCE	34 pF/Ft. Nom.
IMPEDANCE	55 Ohms
TEMPERATURE RATING	0 C to 75 C / 300 Volt

## INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com 
<sup>© Windy City Wire, Coble Technology & Products, LLC.</sup>
All rights reserved.