## PART NUMBER 002320

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

| ■ 0275/0725 FT ●          | SMARTWIRE(TM)       | DEVICE/ZONE                    | A  B  C  D  E  O  1  2  3  4  5  6  7  8  9 | <b>K</b>         | SMARTWIRE<br>GLIDE<br>TECHNOLOGY |
|---------------------------|---------------------|--------------------------------|---|------------------|----------------------------------|
| ABLE SPECIFICAT<br>DESCRI |                     | G 2 twisted Conducto           | rs Bare Copper, Shielded Plenur             | n, UL Listed C(U | L)US CMP                         |
| <b>CONDUCTOR</b> 18 (7/26 |                     | 6 Bare Copper)                 |   |                  |                                  |
| INSULATION Low-Smo        |                     | noke PVC .008"                 |   |                  |                                  |
| COLOR                     | CODE Black/         | Vhite                          | 11.   |                  |                                  |
| LAY LE                    | <b>NGTH</b> 2.5" LF | IL (4.8 TPF)                   |   |                  |                                  |
| S                         | HIELD Alumin        | um Mylar                       |   |                  |                                  |
| DRAIN                     | WIRE 24 AW          | G 7 Strand Tinned Co           | pper  |                  |                                  |
| J                         | ACKET Low-Sr        | noke PVC .018"                 |   |                  |                                  |
| JACKET (                  | COLOR White         | White Jacket                   |   |                  |                                  |
| MAI                       |                     | WIRE DEVICE / ZON<br>N THE USA | E A B C D E 0 1 2 3 4 5 6 7 8               | 9 18 AWG C(      | (UL)US CMP ROHS                  |
| OVERALL DIA               | METER .158" r       | lom.                           |   |                  |                                  |
| CABLE W                   | EIGHT 21 Lbs        | ′Mft.                          |   |                  | ß                                |
| CAPACI                    | FANCE 68 pF/        | 't Nom.                        |   |                  |                                  |
| IMPE                      | DANCE 28 Ohr        | าร                             |   |                  |                                  |
| TEMPERATURE R             | ATING 0 C to        | 75 C / 300 Volt                |   |                  |                                  |

## INDUSTRY STANDARDS

| FLAME RATING     | Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test         |
|------------------|---|
| AGENCY APPROVALS | NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA |



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com 
<sup>© Windy City Wire, Coble Technology & Products, LLC.</sup>
All rights reserved.