PART NUMBER 002322BR

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3 4 5	i 6 7 8 9	K	TECHNOLOGY
ABLE SPECIFICAT		2 Conductor Bare C	opper Shielded Plenum	n, UL Liste	d C(UL)US (CMP
CONDU			,			
INSUL	ATION Low-Sm	Low-Smoke PVC .008"				
COLOR	CODE Black/Re	ed				
S	HIELD Aluminu	m Mylar				
DRAIN	WIRE 24 AWG	7 Strand Tinned Cop	oper			
/נ	ACKET Low-Sm	oke PVC .018"	1 K			
JACKET C	COLOR White J	acket with Blue Strip	e			
MAF		/IRE DEVICE / ZONE I THE USA	A B C D E 0 1 2 3 4	56789	18 AWG	C(UL)US CMP ROHS
OVERALL DIAN	IETER .158" N	om.				
CABLE W	EIGHT 21 Lbs/I	lft.				
CAPACI	FANCE 68 pF/F	. Nom.				ß
IMPEC	DANCE 28 Ohm	5				
TEMPERATURE R	ATING 0 C to 2	'5 C / 300 Volt				

INDUSTRY STANDARDS

WINDY CIT

FLAME RATINGApproved For Plenum Use Without Conduit Per NFPA 262 Flame TestAGENCY APPROVALSNEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WIRE • T 800.379.1191 • windycitywire.com • [©] Windy City Wire, Cable Technology & Products, LLC. All rights reserved.