PART NUMBER 002325

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

| | | | | | SMARTWIRE |
|---------------------------|---------------|--------------------------------|------------------------------|------------------|----------------------|
| ■ 0275/0725 FT ● | SMARTWIRE(TM) | DEVICE/ZONE | A B C D E 0 1 2 3 4 5 6 7 8 | 9 | GLIDE, TECHNOLOGY |
| ABLE SPECIFICAT DESCRI | | 2 twisted Conducto | rs Bare Copper, Shielded Ple | num III Listed (| |
| | | 6 Bare Copper) | | | |
| | | noke PVC .008" | | | |
| COLOR | CODE Black/V | /hite | | | |
| | | L (4.8 TPF) | | | |
| S | HIELD Alumin | um Mylar | | | |
| DRAIN | I WIRE 24 AW | 6 7 Strand Tinned Co | pper | | |
| ſ | ACKET Low-Sr | noke PVC .018" | | | |
| JACKET | COLOR White | Jacket with Purple St | ripe | | |
| MA | | WIRE DEVICE / ZON N THE USA | E A B C D E 0 1 2 3 4 5 6 7 | 789 18 AWG | C(UL)US CMP ROHS |
| OVERALL DIA | METER .158" M | om. | | | |
| CABLE W | EIGHT 21 Lbs | Mft. | | | ß |
| CAPACI | TANCE 68 pF/f | t Nom. | | | |
| IMPE | DANCE 28 Ohr | าร | | | |
| TEMPERATURE R | ATING 0 C to | 75 C / 300 Volt | | | |
| NDUSTRY STAND | ARDS | | | | |

INDUSTRY STANDARDS

| FLAME RATING | Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test |
|------------------|---|
| AGENCY APPROVALS | NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA |



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com
^{© Windy City Wire, Coble Technology & Products, LLC.}
All rights reserved.