PART NUMBER 0023260BR

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE	(TM) DEVICE/ZONE	A B C D E 0 1 2 3 4 5 6 7 8	(The second seco	GLIDE,
CABLE SPECIFICAT	IONS				
DESCRIPTION		18 AWG 2 Conductor Bare Copper Shielded Plenum, UL Listed C(UL)US CMP			
CONDU	JCTOR 1	.8 (7/26 Bare Copper)			
INSUL	ATION L	.ow-Smoke PVC .008"			
COLOR	CODE E	Black/Red			
LAY LE	ENGTH 2	.5" LHL (approx. 4.8 TPF)		
S	HIELD A	luminum Mylar			
DRAIN	WIRE 2	4 AWG 7 Strand Tinned C	opper		
J/	ACKET L	ow-Smoke PVC .018"			
JACKET C	COLOR	Green Jacket			
MAF		MARTWIRE DEVICE / ZOI	NE A B C D E 0 1 2 3 4 5 6	7 8 9 18 AWG C(UL	.)US CMP ROHS
OVERALL DIAM	METER .	158" Nom.			
CABLE W	EIGHT 2	1 Lbs/Mft.			D
CAPACI	TANCE 6	8 pF/Ft. Nom.			ע
IMPEC	DANCE 2	8 Ohms			
DC RESIS	TANCE 6	5.66 Ohms/Mft. maximum	@ 20 C		
TEMPERATURE R/		0 C to 75 C / 300 Volt			

INDUSTRY STANDARDS

FLAME RATINGApproved For Plenum Use Without Conduit Per NFPA 262 Flame TestAGENCY APPROVALSNEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE T 800.379.1191 windycitywire.com © Windy City Wire, Cable Technology & Products, LLC. All rights reserved.