## PART NUMBER 0023280

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWI	RE(TM)	DEVICE/ZONE	ABCDE01	23456789		GLIDE, TECHNOLOGY
ABLE SPECIFICAT DESCRI CONDU	PTION		twisted Conductor 3are Copper)	s Bare Copper, s	Shielded Plenur	n, UL Listed C(l	JL)US CMP
INSUL		•	e PVC .008"				
COLOR	CODE	Black/White					
LAY LE	ENGTH	2.5" LHL (4.8 TPF) Aluminum Mylar 24 AWG 7 Strand Tinned Copper					
S	HIELD						
DRAIN	WIRE						
J	ACKET	Low-Smoke PVC .018"					
JACKET (	COLOR	Pink Jacket					
MAI	RKING	SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 18 AWG C(UL)US CMP ROHS MADE IN THE USA					
OVERALL DIA	METER	.158" Nom	1.				
CABLE W	EIGHT	21 Lbs/Mft.					
CAPACI	TANCE	68 pF/ft Nom.					
IMPE	DANCE	28 Ohms					
TEMPERATURE R	ATING	0 C to 75 C / 300 Volt					

## INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com 
<sup>© Windy City Wire, Coble Technology & Products, LLC.</sup>
All rights reserved.