PART NUMBER 002330

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3 4 5 6 7 8 9		SMARTWIRE GLADE TECHNOLOGY
CABLE SPECIFICAT DESCRI		VG 3 Conductor Bare Co	pper, Shielded Plenum, UL L	isted C(UL)US CL3	Ρ
		/26 Bare Copper)			
INSUL		Smoke PVC .008"			
COLOR	CODE Black	/White/Red			
LAY LE	ENGTH 3.25	LHL (approx. 3.7 TPF)	- Marine 1997		
S	HIELD Alum	num Mylar			
DRAIN	WIRE 24 A	VG 7 Strand Tinned Cop	per		
J	ACKET Low-	Smoke PVC .018"			
JACKET (COLOR Whit	e Jacket			
MAI	RKING SMAI MAD	TWIRE DEVICE / ZONE IN THE USA	A B C D E 0 1 2 3 4 5 6 7	8 9 18 AWG C(U	IL)US CL3P ROHS
OVERALL DIA	METER .168	Nom.			
CABLE W	EIGHT 26 L	s/Mft.			R
CAPACI	TANCE 68 p	/ft Nom.			
IMPE	DANCE 28 0	28 Ohms			
TEMPERATURE R	ATING 0 C	o 75 C / 300 Volt			

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CL3P, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com
^{© Windy City Wire, Coble Technology & Products, LLC.}
All rights reserved.