PART NUMBER 002331

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT •

SMARTWIRE(TM)

DEVICE/ZONE

A B C D E 0 1 2 3 4 5 6 7 8 9





CABLE SPECIFICATIONS

DESCRIPTION 18 AWG 3 Conductor Bare Copper, Shielded Plenum, UL Listed C(UL)US CL3P

CONDUCTOR 18 (7/26 Bare Copper) **INSULATION** Low-Smoke PVC .008"

COLOR CODE Black/White/Red

LAY LENGTH 3.25" LHL (approx. 3.7 TPF)

SHIELD Aluminum Mylar

DRAIN WIRE 24 AWG 7 Strand Tinned Copper

JACKET Low-Smoke PVC .018"

JACKET COLOR White Jacket with Red Stripe

MARKING SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 18 AWG C(UL)US CL3P ROHS

MADE IN THE USA

OVERALL DIAMETER .168" Nom.

CABLE WEIGHT 26 Lbs/Mft.

CAPACITANCE 68 pF/ft Nom.

IMPEDANCE 28 Ohms

TEMPERATURE RATING 0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

FLAME RATING Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test

AGENCY APPROVALS NEC Article 800; UL Listed C(UL)US CL3P, RoHs Compliant, Made in the USA







All specifications referenced are nominal measurements unless otherwise noted.