

PART NUMBER 0023330

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable



CABLE SPECIFICATIONS

DESCRIPTION	18 AWG 3 Conductor Bare Copper, Shielded Plenum, UL Listed C(UL)US CL3P
CONDUCTOR	18 (7/26 Bare Copper)
INSULATION	Low-Smoke PVC .008"
COLOR CODE	Black/White/Red
LAY LENGTH	3.25" LHL (approx. 3.7 TPF)
SHIELD	Aluminum Mylar
DRAIN WIRE	24 AWG 7 Strand Tinned Copper
JACKET	Low-Smoke PVC .018"
JACKET COLOR	Yellow Jacket
MARKING	SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 18 AWG C(UL)US CL3P ROHS MADE IN THE USA
OVERALL DIAMETER	.168" Nom.
CABLE WEIGHT	26 Lbs/Mft.
CAPACITANCE	68 pF/ft Nom.
IMPEDANCE	28 Ohms
TEMPERATURE RATING	0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CL3P, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.