PART NUMBER 002353-500

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM) DEVICE/ZONE A B C D E 0 1 2 3 4 5 6 7 8 9	
ABLE SPECIFICA	TIONS	
DESCR	IPTION 18 AWG 10 Conductor Bare Copper, Shielded Plenum, UL Listed C(UL)US CN	4P
CONE	DUCTOR 18 (7/26 Bare Copper)	
INSU	LATION Low-Smoke PVC .008"	
COLO	R CODE Black/White/Red/Green/Brown/Blue/Orange/Yellow/Purple/Gray	
LAY I	LENGTH 4" LHL (approx. 3 TPF)	
	SHIELD Aluminum Mylar	
DRAI	N WIRE 24 AWG 7 Strand Tinned Copper	
	JACKET Low-Smoke PVC .018"	
JACKET	COLOR White Jacket	
M	ARKING SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 18 AWG C(MADE IN THE USA	(UL)US CMP ROH
OVERALL DI	AMETER .258" Nom.	
CABLE V	NEIGHT 79 Lbs/Mft.	R
CAPAC	ITANCE 68 pF/ft Nom.	
IMPE	EDANCE 28 Ohms	
TEMPERATURE I	RATING 0 C to 75 C / 300 Volt	

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com
^{© Windy City Wire, Coble Technology & Products, LLC.}
All rights reserved.