## PART NUMBER 002360BR

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3 4 5	6789	
BLE SPECIFICAT		2 Conductor Pore C	annar Nan Chielded Die		
		G 2 Conductor Bare Copper, Non-Shielded Plenum, UL Listed C(UL)US CMP 26 Bare Copper)			
		oke PVC .008"			
COLOR					
S	HIELD N/A				
DRAIN	WIRE N/A				
ſ	ACKET Low-Sm	oke PVC .018"			
JACKET	COLOR White	acket			
MA		VIRE DEVICE / ZONE N THE USA	A B C D E 0 1 2 3 4	56789 18A	AWG C(UL)US CMP ROHS
OVERALL DIA	METER .158" N	om.			
CABLE W	EIGHT 16 Lbs/	Mft.			
CAPACI	TANCE 27 pF/F	t. Nom.			ß
IMPE	DANCE 70 Ohm	s			
DC RESIS	<b>FANCE</b> 6.66 Of	6.66 Ohms/Mft. maximum @ 20 C			
TEMPERATURE R	ATING 0 C to	75 C / 300 Volt			

## **INDUSTRY STANDARDS**

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com 
<sup>© Windy City Wire, Coble Technology & Products, LLC.</sup>
All rights reserved.