PART NUMBER 002376

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3	456789		N O L O G Y
ABLE SPECIFICAT DESCRIF		3 Conductor Bare Co	oper, Non-Shielded	d Plenum, UL Li	sted C(UL)US CMP	
CONDU	ICTOR 18 (7/2	6 Bare Copper)				
INSUL	ATION Low-Sr	noke PVC .008"				
COLOR	CODE Black/V	/hite/Red	11 C C			
LAY LE	NGTH 3.25" L	HL (approx. 3.7 TPF)				
SI	HIELD N/A					
DRAIN	WIRE N/A					
4٢	ACKET Low-Sr	noke PVC .018"				
JACKET C	COLOR White	lacket with Green Strip	be and a second s			
MAF	RKING SMART MADE 1	WIRE DEVICE / ZONE N THE USA	A B C D E 0 1 2 3	8 4 5 6 7 8 9	18 AWG C(UL)US CM	1P ROHS
OVERALL DIAN	168" N	om.				
CABLE WI	EIGHT 23 Lbs,	23 Lbs/Mft.				
CAPACIT	TANCE 27 pF/I	t. Nom.				
IMPEC	ANCE 70 Ohr	IS				
TEMPERATURE RA	ATING 0 C to	75 C / 300 Volt				

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com
^{© Windy City Wire, Coble Technology & Products, LLC.}
All rights reserved.