## PART NUMBER 002378

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3 4 5 6 7 8 9	TECHNOLOGY
ABLE SPECIFICAT DESCRI CONDU	PTION 18 AWG	3 Conductor Bare Co 5 Bare Copper)	opper, Non-Shielded Plenum, l	JL Listed C(UL)US CMP
INSUL COLOR	ATION Low-Sm	oke PVC .008" hite/Red		
LAY LE S	ENGTH 3.25" LI HIELD N/A	3.25" LHL (approx. 3.7 TPF)		
-	ACKET Low-Sm	oke PVC .018"	11 .	
JACKET ( MAI	RKING SMART	acket with Pink Strip VIRE DEVICE / ZONE I THE USA		9 18 AWG C(UL)US CMP ROHS
OVERALL DIAI CABLE W		.168" Nom. 23 Lbs/Mft. 27 pF/Ft. Nom. 70 Ohms		
CAPACI" IMPEI				
TEMPERATURE R	ATING 0 C to	75 C / 300 Volt		

## INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com 
<sup>© Windy City Wire, Coble Technology & Products, LLC.</sup>
All rights reserved.