PART NUMBER 002379

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

■ 0275/0725 FT ● SMAI	TWIRE(TM) DEVICE/ZONE A B C D E 0 1 2 3 4 5 6 7 8 9
CABLE SPECIFICATION DESCRIPTION CONDUCTO INSULATION COLOR COD LAY LENGT	 18 AWG 3 Conductor Bare Copper, Non-Shielded Plenum, UL Listed C(UL)US CMP 18 (7/26 Bare Copper) Low-Smoke PVC .008" Black/White/Red
SHIEL DRAIN WIR	, , , , , , , , , , , , , , , , , , ,
JACKE	
JACKET COLO	R Blue Jacket
MARKIN	SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 18 AWG C(UL)US CMP ROHS MADE IN THE USA
OVERALL DIAMETE	R .168" Nom.
CABLE WEIGH	23 Lbs/Mft.
CAPACITANC	27 pF/Ft. Nom.
IMPEDANC	70 Ohms
TEMPERATURE RATIN	G 0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com
^{© Windy City Wire, Coble Technology & Products, LLC.}
All rights reserved.