PART NUMBER 002380

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

| | | | | | | | SMARTWIRE |
|------------------|---------|--|-----------------------------|-----------------------|-------------|---------|----------------------|
| ■ 0275/0725 FT ● | SMARTW | IRE(TM) | DEVICE/ZONE | A B C D E 0 1 2 3 4 | 56789 | | GLIDE, TECHNOLOGY |
| ABLE SPECIFICA | TIONS | | | | | | |
| DESCRIPTION | | 18 AWG 4 Conductor Bare Copper, Non-Shielded Plenum, UL Listed C(UL)US CMP | | | | | |
| CONI | DUCTOR | 18 (7/26 Bare Copper) | | | | | |
| INSU | LATION | DN Low-Smoke PVC .008" | | | | | |
| COLO | OR CODE | Black/White/Red/Green | | | | | |
| LAY | LENGTH | 3.5" LHL | (approx. 3.4 TPF) | 11. A. | | | |
| | SHIELD | N/A | | | | | |
| DRAI | N WIRE | N/A | | 6 K | | | |
| | JACKET | Low-Smo | ke PVC .018" | | | | |
| JACKET | COLOR | White Ja | cket | | | | |
| M | ARKING | SMARTWI | RE DEVICE / ZONI THE USA | E A B C D E 0 1 2 3 4 | 56789 | 18 AWG | C(UL)US CMP ROHS |
| OVERALL DI | AMETER | .184" Nor | n. | | | | |
| CABLE | WEIGHT | 32 Lbs/M | ft. | | | | R |
| САРАС | TANCE | 26 pF/Ft. | Nom. | | _ | | |
| IMP | EDANCE | 72 Ohms | | | | | |
| DC RESI | STANCE | 6.66 Ohm | ns/Mft. maximum @ | 0 20 C | | | |
| TEMPERATURE | RATING | 0 C to 75 | C / 300 Volt | | | | |
| NDUSTRY STAN | DARDS | | | | | | |
| FLAME | RATING | Approved | For Plenum Use W | ithout Conduit Per NF | PA 262 Flai | me Test | |

AGENCY APPROVALS

NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

