PART NUMBER 002392

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTW	IRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3 4 5	6789	SMARTWIRE GLIDE TECHNOLOGY
ABLE SPECIFICA						
	IPTION			Copper, Non-Shielded Ple	enum, UL Listed C(UL)US CMP
CONDUCTOR		18 (7/26 Bare Copper)				
INSULATION		Low-Smoke PVC .008"				
COLO	R CODE	Black/White/Red/Green/Brown/Blue/Orange/Yellow				
LAY	LENGTH	3.75" LHI	L (approx. 3.2 TPF)			
	SHIELD	N/A				
DRAI	N WIRE	N/A				
	JACKET	Low-Smo	ke PVC .018"			
JACKET	COLOR	White Ja	cket			
M	ARKING		IRE DEVICE / ZON THE USA	E A B C D E 0 1 2 3 4 1	56789 18 AW	G C(UL)US CMP ROHS
OVERALL DI	AMETER	.234" No	m.			
CABLE V	WEIGHT	62 Lbs/M	ft.			
САРАС		27 pF/Ft.	Nom			
IMPI	EDANCE	70 Ohms				
DC RESI	STANCE	6.66 Ohn	ns/1000ft max @ 2	0 C		
TEMPERATURE			5 C / 300 Volt			
INDUSTRY STAN	DARDS					

FLAME RATING

WINDY CITY

Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WIRE • T 800.379.1191 • windycitywire.com • [©] WindyCityWire, Cable Technology & Products, LLC. All rights reserved.