PART NUMBER 003360

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3 4 5	56789	C SMARTWIRE GLIDE TECHNOLOGY
ABLE SPECIFICAT DESCRI		6 2 Conductor Bare Co	nnor Non Shieldod D	Jonum III Listed C	
		8 Bare Copper)	pper, Non-Smelded P	ienum, of fisted c	
INSUL		noke PVC .008"			
COLOR	CODE Black/\	/hite			
LAY LI	ENGTH 2.75" L	HL (approx. 4.36 TPF)			
S	HIELD N/A				
DRAIN	WIRE N/A				
ſ	ACKET Low-Sr	noke PVC .018"			
JACKET	COLOR White	Jacket			
MA		WIRE DEVICE / ZONE N THE USA	A B C D E 0 1 2 3 4	56789 20 AV	VG C(UL)US CMP ROHS
OVERALL DIA	METER .140"	om.			
CABLE W	EIGHT 13 Lbs,	Mft.			R
CAPACI	TANCE 25 pF/	t. Nom.			
IMPE	DANCE 75 Ohr	ns			
TEMPERATURE R	ATING 0 C to	75 C / 300 Volt			

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com
^{© Windy City Wire, Coble Technology & Products, LLC.}
All rights reserved.