PART NUMBER 004321

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(M) DEVICE/ZONE	A B C D E 0 1 2 3 4 5 6 7 8 9		C H N O L O G Y
			onnen Chielded Dianum III I i		
DESCRI		(7/30 Bare Copper)	opper, Shielded Plenum, UL Li	Sted C(UL)US CMP	
INSUL		w-Smoke PVC .008"			
COLOR		ack/White			
		5" LHL (approx. 4.8 TPF)			
		uminum Mylar	en		
DRAIN		AWG 7 Strand Tinned Co	oper		
		w-Smoke PVC .018"			
JACKET (COLOR V	hite Jacket with Red Strip	e		
МАІ	RKING SI		E A B C D E 0 1 2 3 4 5 6 7 8	3 9 22 AWG C(UL	.)US CMP ROHS
OVERALL DIA	METER .1	26" Nom.			
CABLE W	EIGHT 12	Lbs/Mft.			ລ
CAPACI	TANCE 51	pF/ft Nom.			
IMPE	DANCE 37	' Ohms			
TEMPERATURE R	ATING 0	C to 75 C / 300 Volt			
INDUSTRY STAND	ARDS				

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com
^{© Windy City Wire, Coble Technology & Products, LLC.}
All rights reserved.