PART NUMBER 0043230

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3 4	456789		SMARTWIRE GLIDE TECHNOLOGY	
CABLE SPECIFICAT DESCRII		2 Conductor Bare Co	opper, Shielded Plen	um, UL Liste	d C(UL)US CMP	,	
CONDUCTOR 22 (7/30		/30 Bare Copper)					
INSULATION Low-Smo		oke PVC .008"					
COLOR	CODE Black/W	hite	1.1				
LAY LE	NGTH 2.5" LH	2.5" LHL (approx. 4.8 TPF)					
S	HIELD Aluminu	Aluminum Mylar					
DRAIN	WIRE 24 AWG	24 AWG 7 Strand Tinned Copper					
/נ	ACKET Low-Sm	Low-Smoke PVC .018"					
JACKET C	COLOR Yellow	Yellow Jacket					
MAF		SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 22 AWG C(UL)US CMP ROHS MADE IN THE USA					
OVERALL DIAM	METER .126" N	.126" Nom.					
CABLE W	EIGHT 12 Lbs/	12 Lbs/Mft.					
CAPACIT	TANCE 51 pF/ft	Nom.		_			
IMPEC	DANCE 37 Ohm	s					
TEMPERATURE R	ATING 0 C to	75 C / 300 Volt					

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com
^{© Windy City Wire, Coble Technology & Products, LLC.}
All rights reserved.