PART NUMBER 0043250

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3 4 5 6 7 8	8 9	SMARTWIRE GLIDE TECHNOLOGY
CABLE SPECIFICAT DESCRI		i 2 Conductor Bare Co	opper, Shielded Plenum, UL	Listed C(UL)US CN	٩P
	CONDUCTOR 22 (7/30 INSULATION Low-Smo				
COLOR LAY LE	,	Black/White 2.5" LHL (approx. 4.8 TPF)			
S DRAIN		Aluminum Mylar 24 AWG 7 Strand Tinned Copper			
JACKET (Low-Smoke PVC .018" Purple Jacket			
MAI OVERALL DIAI	MADE 1	SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 22 AWG C(UL)US CMP ROHS MADE IN THE USA .126" Nom.			
CABLE W	EIGHT 12 Lbs/	12 Lbs/Mft.			
CAPACI IMPEI	DANCE 37 Ohn	51 pF/ft Nom. 37 Ohms 0 C to 75 C / 300 Volt			
TEMPERATURE RA	ATING 0 C to				

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com
^{© Windy City Wire, Coble Technology & Products, LLC.}
All rights reserved.