PART NUMBER 004330

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM) DEVICE/ZONE	A B C D E 0 1 2 3 4 5 6 7	789	SMARTWIRE GLIDE TECHNOLOGY
CABLE SPECIFICA DESCRI		2 AWG 3 Conductor Bare Co	pper, Shielded Plenum, L	JL Listed C(UL)US (CMP
COND	UCTOR 2	2 (7/30 Bare Copper)			
INSUL	LATION Lo	ow-Smoke PVC .008"			
COLOF	R CODE B	ack/White/Red	11 C		
LAY L	ENGTH 2	5" LHL (approx. 4.8 TPF)			
S	SHIELD A	luminum Mylar			
DRAIN	N WIRE 24	4 AWG 7 Strand Tinned Cop	ber		
נ	JACKET Lo	ow-Smoke PVC .018"			
JACKET	COLOR V	Vhite Jacket			
МА		MARTWIRE DEVICE / ZONE ADE IN THE USA	A B C D E 0 1 2 3 4 5 6	5789 22 AWG	C(UL)US CMP ROHS
OVERALL DIA	METER .1	.34" Nom.			
CABLE W	VEIGHT 1	5 Lbs/Mft.			ß
CAPACI	TANCE 5	0 pF/ft Nom.			
IMPE	DANCE 3	8 Ohms			
TEMPERATURE R	RATING (C to 75 C / 300 Volt			

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com
^{© Windy City Wire, Coble Technology & Products, LLC.}
All rights reserved.