PART NUMBER 004340-110

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Pro A/V

| ■ 0275/0725 FT ● SM | IARTWIRE(TM) PRO A/V A B C D E O 1 2 3 4 5 6 7 8 9 |
|----------------------|---|
| CABLE SPECIFICATIONS | |
| DESCRIPTION | 22 AWG 4 Conductor Bare Copper, Shielded Plenum, UL Listed C(UL)US CMP |
| CONDUCTOR | 22 (7/30 Bare Copper) |
| INSULATION | Low-Smoke PVC .008" |
| COLOR CODE | Black/Red/Yellow/Green |
| SHIELD | Aluminum Mylar |
| DRAIN WIRE | 24 AWG 7 Strand Tinned Copper |
| JACKET | Low-Smoke PVC .018" |
| JACKET COLOR | Black Jacket |
| MARKING | SMARTWIRE PRO A/V A B C D E 0 1 2 3 4 5 6 7 8 9 22 AWG C(UL)US CMP ROHS MADE IN THE USA |
| OVERALL DIAMETER | .145" Nom. |
| CABLE WEIGHT | 19 Lbs/Mft. |
| CAPACITANCE | 51 pF/Ft. Nom. |
| IMPEDANCE | 37 Ohms |
| TEMPERATURE RATING | 0 C to 75 C / 300 Volt |
| INDUSTRY STANDARDS | |

STANDARDS) I K I

WINDY CIT

Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test FLAME RATING AGENCY APPROVALS NEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WIRE • T 800.379.1191 • windycitywire.com • [©] WindyCityWire.^{Cable Technology & Products, LLC. All rights reserved.}