PART NUMBER 004344

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TN	DEVICE/ZONE	A B C D E 0 1 2 3 4 5 6 7 8	9	TECHNOLOGY)
BLE SPECIFICA		WC 4 Conductor Bara Co	pper, Shielded Plenum, UL	Listod C(111)US (CMD
		7/30 Bare Copper)	oper, Shielded Fieldin, OL		
	·	Smoke PVC .008"			
		<td></td> <td></td> <td></td>			
		LHL (approx. 4.8 TPF)			
		ninum Mylar	en		
		WG 7 Strand Tinned Cop	ber		
		Smoke PVC .018"			
JACKET		te Jacket with Orange Str	ine		
	RKING SMA		A B C D E 0 1 2 3 4 5 6	78922AWG	C(UL)US CMP ROHS
OVERALL DIA	METER .145	" Nom.			
CABLE W	EIGHT 19 L	bs/Mft.			
CAPACI	TANCE 50 p	F/ft Nom.			B
IMPE	DANCE 37 (hms			
DC RESIS	TANCE 16.9	Ohms/Mft. maximum @	20 C		
TEMPERATURE R	ATING 0 C	to 75 C / 300 Volt			

INDUSTRY STANDARDS

FLAME RATINGApproved For Plenum Use Without Conduit Per NFPA 262 Flame TestAGENCY APPROVALSNEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE T 800.379.1191 windycitywire.com © Windy City Wire, Cable Technology & Products, LLC. All rights reserved.