PART NUMBER 004346

ETL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(1	TM) DEVICE/ZONE	A B C D E 0 1 2 3 4	456789		SMARTWIRE GLIDE TECHNOLOGY
ABLE SPECIFICAT DESCRI		2 AWG 4 Conductor Bare Co	opper, Shielded Plen	um, UL Liste	ed C(UL)US CM	D
COND		2 (7/30 Bare Copper)				
INSUL	ATION La	w-Smoke PVC .008"				
COLOR	R CODE BI	ack/Red/White/Green				
S	SHIELD AI	uminum Mylar				
DRAIN	WIRE 24	AWG 7 Strand Tinned Cop	oper			
J	IACKET La	w-Smoke PVC .018"				
JACKET	COLOR W	/hite Jacket with Green Str	ipe			
MA		ARTWIRE DEVICE / ZONE	A B C D E 0 1 2 3	456789	9 22 AWG C(I	UL)US CMP ROHS
OVERALL DIA	METER .1	45" Nom.				
CABLE W	EIGHT 19	Lbs/Mft.				
CAPACI	TANCE 51	. pF/Ft. Nom.				R
IMPE	DANCE 37	' Ohms		_		
TEMPERATURE R	ATING 0	C to 75 C / 300 Volt				

INDUSTRY STANDARDS

WINDY CIT

FLAME RATINGApproved For Plenum Use Without Conduit Per NFPA 262 Flame TestAGENCY APPROVALSNEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WIRE • T 800.379.1191 • windycitywire.com • [©] Windy City Wire, Cable Technology & Products, LLC. All rights reserved.