PART NUMBER 004352-110

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ● SMART	WIRE(TM) DEVICE/ZONE A B C D E 0 1 2 3 4 5 6 7 8 9
CABLE SPECIFICATIONS	
DESCRIPTION	22 AWG 8 Conductor Bare Copper, Shielded Plenum, UL Listed C(UL)US CMP
CONDUCTOR	22 (7/30 Bare Copper)
INSULATION	Low-Smoke PVC .008"
COLOR CODE	Black/Red/White/Green/Brown/Blue/Orange/Yellow
SHIELD	Aluminum Mylar
DRAIN WIRE	24 AWG 7 Strand Tinned Copper
JACKET	Low-Smoke PVC .018"
JACKET COLOR	Black Jacket
MARKING	SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 22 AWG C(UL)US CMP ROHS MADE IN THE USA
OVERALL DIAMETER	.182" Nom.
CABLE WEIGHT	31 Lbs/Mft.
CAPACITANCE	51 pF/Ft. Nom.
IMPEDANCE	37 Ohms
TEMPERATURE RATING	0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

WINDY CITY

 FLAME RATING
 Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test

 AGENCY APPROVALS
 NEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WIRE • T 800.379.1191 • windycitywire.com • [©] Windy City Wire, Cable Technology & Products, LLC. All rights reserved.