PART NUMBER 004360

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3 4 5	6789	SMARTWIRE GLIDE TECHNOLOGY
ABLE SPECIFICAT DESCRI		6 2 Conductor Bare Co	pper, Non-Shielded Pl	enum, UL Listed (C(UL)US CMP
COND	UCTOR 22 (7/3	0 Bare Copper)			
INSUL	ATION Low-Sr	noke PVC .008"			
COLOR	R CODE Black/W	/hite	1.1		
LAY L	ENGTH 2.5" LH	L (approx. 4.8 TPF)			
s	SHIELD N/A				
DRAIN	I WIRE N/A				
ſ	ACKET Low-Sr	noke PVC .018"			
JACKET	COLOR White	Jacket			
MA		WIRE DEVICE / ZONE N THE USA	A B C D E 0 1 2 3 4	56789 22 AV	WG C(UL)US CMP ROHS
OVERALL DIA	METER .126" N	om.			
CABLE W	EIGHT 9 Lbs/N	lft.			ß
CAPACI	TANCE 20 pF/F	t. Nom.			
IMPE	DANCE 94 Ohn	IS			
TEMPERATURE R	ATING 0 C to	75 C / 300 Volt			

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

