PART NUMBER 0043730

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3 4 5 6 7	89	SMARTWIRE GLIDE TECHNOLOGY
ABLE SPECIFICAT DESCRI CONDU INSULA COLOR LAY LE S	PTION22 AWGJCTOR22 (7/3ATIONLow-SmCODEBlack/W	3 Conductor Bare C D Bare Copper) oke PVC .008" 'hite/Red - (approx. 4.8 TPF)	opper, Non-Shielded Plenu	m, UL Listed C(UL	.)US CMP
DRAIN	WIRE N/A	N/A			
JACKET (Low-Smoke PVC .018" Yellow Jacket			
MAI		VIRE DEVICE / ZONI N THE USA	E A B C D E 0 1 2 3 4 5 6	789 22 AWG	C(UL)US CMP ROHS
OVERALL DIA	METER .134" N	om.			
CABLE W	EIGHT 13 Lbs/	Mft.			ß
CAPACI	TANCE 20 pF/F	t. Nom.			
IMPE	DANCE 94 Ohm	94 Ohms			
TEMPERATURE RA	ATING 0 C to	75 C / 300 Volt			

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com
^{© Windy City Wire, Coble Technology & Products, LLC.}
All rights reserved.