## PART NUMBER 004381

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWI	RE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3 4 5 6	789		
ABLE SPECIFICAT DESCRII		22 AWG	4 Conductor Bare C	opper, Non-Shielded Plei	num, UL List	ed C(UL)US	5 СМР
CONDU			Bare Copper)		- ,		
INSUL	ATION	Low-Sm	oke PVC .008"				
COLOR	CODE	Black/Re	d/White/Green				
S	HIELD	N/A					
DRAIN	WIRE	N/A					
J	ACKET	Low-Sm	oke PVC .018"				
JACKET O	COLOR	White Ja	acket with Red Strip	e			
МАГ	RKING		IRE DEVICE / ZONE	E A B C D E 0 1 2 3 4 5	56789	22 AWG C(	UL)US CMP ROHS
OVERALL DIAN	METER	.145" No	m.				
CABLE W	EIGHT	15 Lbs/N	lft.				
CAPACI	TANCE	20 pF/Ft	. Nom.				ß
IMPE	DANCE	94 Ohms			_		
TEMPERATURE R	ATING	0 C to 7	5 C / 300 Volt				
NDUSTRY STAND	ARDS						
FLAME R	ATING	Approve	d For Plenum Use W	ithout Conduit Per NFPA	262 Flame T	Fest	

NEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA

AGENCY APPROVALS



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com 
<sup>© Windy City Wire, Coble Technology & Products, LLC.</sup>
All rights reserved.