PART NUMBER 004386-500

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM)	DEVICE/ZONE A B C D E 0 1 2 3 4 5 6 7 8 9	
BLE SPECIFICAT			
DESCRI		3 4 Conductor Bare Copper, Non-Shielded Plenum, Ul	L Listed C(UL)US CMP
		0 Bare Copper)	
INSUL	ATION Low-S	noke PVC .008"	
COLOR	CODE Black/	/hite/Red/Green	
LAY L	ENGTH 2.5" LI	L (approx. 4.8 TPF)	
S	HIELD N/A		
DRAIN	WIRE N/A		
J	ACKET Low-S	noke PVC .018"	
JACKET	COLOR White	Jacket with Green Stripe	
MA		NIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 N THE USA	9 22 AWG C(UL)US CMP ROHS
OVERALL DIA	METER .145"	om.	
CABLE W	EIGHT 16 Lbs	Mft.	ß
CAPACI	TANCE 20 pF/	t. Nom.	
IMPE	DANCE 94 Oh	IS	
DC RESIS	TANCE 16.9 C	nms/Mft. maximum @ 20 C	
TEMPERATURE R	ATING 0 C to	75 C / 300 Volt	

INDUSTRY STANDARDS

FLAME RATINGApproved For Plenum Use Without Conduit Per NFPA 262 Flame TestAGENCY APPROVALSNEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

