PART NUMBER 004386

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM	I) DEVICE/ZONE A B C D E O 1 2 3 4 5 6 7 8 9
BLE SPECIFICA		
		WG 4 Conductor Bare Copper, Non-Shielded Plenum, UL Listed C(UL)US CMP
		7/30 Bare Copper)
INSU	LATION Low	-Smoke PVC .008"
COLO	R CODE Blac	k/White/Red/Green
LAY I	ENGTH 2.5"	LHL (approx. 4.8 TPF)
:	SHIELD N/A	
DRAI	N WIRE N/A	
	JACKET Low	-Smoke PVC .018"
JACKET	COLOR Wh	ite Jacket with Green Stripe
MA		RTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 22 AWG C(UL)US CMP ROHS DE IN THE USA
OVERALL DIA	METER .145	5" Nom.
CABLE V	VEIGHT 16 L	bs/Mft.
CAPAC	TANCE 20 p	oF/Ft. Nom.
IMPE	DANCE 94 0	Dhms
DC RESIS	5TANCE 16.9	9 Ohms/Mft. maximum @ 20 C
TEMPERATURE F	RATING 0 C	to 75 C / 300 Volt

INDUSTRY STANDARDS

FLAME RATINGApproved For Plenum Use Without Conduit Per NFPA 262 Flame TestAGENCY APPROVALSNEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

