PART NUMBER 007920

UL Listed and Rated Type CL3P Multi-Conductor Shielded Plenum Cable

| ■ 0275/0725 FT ● | SMARTWIRE | E(TM) | DEVICE/ZONE | A B C D E 0 1 2 3 | 3 4 5 6 7 8 9 | K | SMARTWIRE GLIDE TECHNOLOGY | |
|------------------|-----------|--|-----------------------|-------------------|---------------|-------------|----------------------------------|--|
| CABLE SPECIFICAT | IONS | | | | | | | |
| DESCRIPTION | | 14 AWG 2 Conductor Bare Copper, Shielded Plenum, UL Listed (UL) CL3P | | | | | | |
| CONDU | JCTOR : | 14 (19/27 E | 4 (19/27 Bare Copper) | | | | | |
| INSUL | ATION I | Low-Smoke PVC .008" | | | | | | |
| COLOR | CODE | Black/White | 2 | 11 C C | | | | |
| s | HIELD / | Aluminum N | lylar | ш. – | | | | |
| DRAIN | WIRE 2 | 22 AWG 7 Strand Tinned Copper | | | | | | |
| J | ACKET I | Low-Smoke | PVC .018" | | | | | |
| JACKET (| COLOR | White Jack | et | | | | | |
| MAI | | SMARTWIRI | | A B C D E 0 1 2 3 | 3 4 5 6 7 8 9 | 14 AWG (UL) | CL3P ROHS MADE | |
| OVERALL DIA | METER . | .210" Nom. | | | | | | |
| CABLE W | EIGHT 4 | 44 Lbs/Mft. | | | | | | |
| CAPACI | TANCE | 90 pF/Ft. N | om. | | | | ß | |
| IMPE | DANCE | 21 Ohms | | | | | | |
| TEMPERATURE R | ATING | 0 C to 75 C | C / 300 Volt | | | | | |

INDUSTRY STANDARDS

WINDY CITY

FLAME RATINGApproved For Plenum Use Without Conduit Per NFPA 262 Flame TestAGENCY APPROVALSNEC Article 800; UL Listed (UL) CL3P, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WIRE • T 800.379.1191 • windycitywire.com • ^{© Windy City Wire, Cable Technology & Products, LLC.} All rights reserved.