

PART NUMBER 042007DB


Non-UL Listed Single Pair Shielded Low-Cap Non-Plenum Direct Burial Cable

DIRECT BURIAL

SUNLIGHT RESISTANT

24 AWG SHIELDED

LOW CAP 12.5pF



CABLE SPECIFICATIONS

DESCRIPTION	1 Pair, 24 AWG Tinned Copper Shielded RS-232, RS-422, RS-485 Low-Capacitance Communication, Instrumentation and Special Application Direct Burial Non-UL Cable
CONDUCTOR	24 AWG (7/32) Tinned Copper
INSULATION	Foam Polyethylene .016"
COLOR CODE	Black/White
SHIELD	Aluminum Mylar
DRAIN WIRE	24 AWG Stranded Tinned Copper
JACKET	Black PE .020"
JACKET COLOR	Black Jacket
MARKING	LO-CAP 12.5 Pf/FT DIRECT BURIAL 24 AWG 1 PAIR SHIELDED
OVERALL DIAMETER	.156" Nom.
CABLE WEIGHT	16 Lbs/Mft.
CAPACITANCE	12.5 pF/Ft. Nom.
IMPEDANCE	100 Ohms/Mft.
TEMPERATURE RATING	-40 C to 75 C
VOLTAGE RATING	300 Volts Max.

INDUSTRY STANDARDS

AGENCY APPROVALS None



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC.
All rights reserved.