


# PART NUMBER 043006ALDB

■ 0275/0725 FT ●

ARC 156

A B C D E 0 1 2 3 4 5 6 7 8 9



## CABLE SPECIFICATIONS

<b>DESCRIPTION</b>	1 Pair, 22 AWG Tinned Copper Shielded RS-232, RS-422, RS-485 Low-Capacitance Communication Instrumentation and Special Application Direct Burial Cable, Sunlight Resistant
<b>CONDUCTOR</b>	22 AWG (7/30) Tinned Copper
<b>INSULATION</b>	Foam PE, .0155"
<b>COLOR CODE</b>	Black/White
<b>LAY LENGTH</b>	1.5" Lay
<b>SHIELD</b>	Aluminum Mylar
<b>DRAIN WIRE</b>	24 AWG 7 Strand Tinned Copper
<b>JACKET</b>	High Density Polyethylene, .035"
<b>JACKET COLOR</b>	Black Jacket
<b>MARKING</b>	ARC 156 A B C D E 0 1 2 3 4 5 6 7 8 9 MADE IN USA
<b>OVERALL DIAMETER</b>	.199" Nom.
<b>CABLE WEIGHT</b>	13.6 lbs/mft.
<b>CAPACITANCE</b>	12.5 pF/ft.
<b>IMPEDANCE</b>	100 ohms
<b>DC RESISTANCE</b>	15 ohms/mft.
<b>TEMPERATURE RATING</b>	60 C / 300 Volt

## INDUSTRY STANDARDS

**AGENCY APPROVALS** Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.



**WINDY CITY WIRE** • T 800.379.1191 • [windycitywire.com](http://windycitywire.com)

© Windy City Wire, Cable Technology & Products, LLC.  
All rights reserved.