PART NUMBER 061009

UL Listed and Rated Type CMP Category 3 Non-Shielded Plenum Cable

■ 0275/0725 FT •

24 AWG CMP C(UL) IEEE 802.3 10 BASE T CAT 3 ROHS



CABLE SPECIFICATIONS

DESCRIPTION 24 AWG Category 3 Unshielded Twisted Pair (UTP) Cable for Data Transmissions. This Cable is

Plenum Rated and Verified to Category 3 Electricals

24 (Solid Bare Copper) **CONDUCTOR**

Plenum PVC .0038" **INSULATION**

COLOR CODE Blue-White/White-Blue

Orange-White/White-Orange

Green-White/White-Green

Plenum PVC **JACKET**

JACKET COLOR Blue Jacket

> **MARKING** E106583 (01-12345) 24 AWG CMP C(UL)US --- IEEE 802.3 10BASE T --- ETL VERIFIED TO

ANSI/TIA-568-C.2 CAT3 RoHS 0/1000

OVERALL DIAMETER .158" Nom.

> CABLE WEIGHT 16 Lbs/Mft.

CAPACITANCE 17.5 pF/Ft. Nom

IMPEDANCE 100 Ohms Nominal

DC RESISTANCE 27 Ohms/Kft

TEMPERATURE RATING 75 C / 300 Volt

> **VOLTAGE RATING** 300 Volts

INDUSTRY STANDARDS

FLAME RATING NFPA 262, Plenum Fire Test (UL 190)

AGENCY APPROVALS UL Type CMP C(UL)US

UL 444, Communications Cables ICEA S-80-576 and NEC Article 800 California State Fire Marshal Approved

RoHS Compliant







All specifications referenced are nominal measurements unless otherwise noted.