## PART NUMBER 105500

UL Listed and Rated Type CMP Single Pair Non-Shielded Echelon Compliant Plenum Cable

CABLE SPECIFICATIONS   DESCRIPTION 22 AWG Unshielded Twisted 1 Pair (UTP) Cable for Data Transmission. This cable is plenum rated.   CONDUCTOR 22 AWG (7/30) Bare Copper   INSULATION White/Blue Cond: Low-Smoke PVC; Blue Cond: FEP   COLOR CODE White-Blue/Blue	
INSULATION White/Blue Cond: Low-Smoke PVC; Blue Cond: FEP	
COLOR CODE White-Blue/Blue	
LAY LENGTH 2.5" LHL (approx. 4.8 TPF)	
SHIELD N/A	
DRAIN WIRE N/A	
JACKET Low-Smoke PVC .015" Nom.	
JACKET COLOR Blue Jacket	
MARKING ECHELON GUIDELINE COMPLIANT ZONE BUS / COMM LINE A B C D E 0 1 2 3 4 5 6 7 8 9 22 AWG C(UL)US CMP ROHS MADE IN THE USA	
OVERALL DIAMETER .133" Nom.	
CABLE WEIGHT 10 Lbs/Mft.	
CAPACITANCE 17 pF/ft.	
IMPEDANCE 100 Ohms	
TEMPERATURE RATING 0 C to 75 C / 300 Volt	
INDUSTRY STANDARDS	
FLAME RATING   Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test     ACENEX APPROVALE   NEC Article 2000 Htt Listed C(Htt)/UC CMD. Construction for the MCA	
AGENCY APPROVALS NEC Article 800; UL Listed C(UL)US CMP, Communication Cable, Made in the USA	

All specifications referenced are nominal measurements unless otherwise noted.

