


PART NUMBER 108760DB

■ 0275/0725 FT ● TEMPERATURE CONTROL SYSTEM ZONE BUS/COMM LINE ABCDE0123456789



CABLE SPECIFICATIONS

DESCRIPTION	18 AWG 1 Pair Tinned Copper Shielded, Direct Burial Cable
CONDUCTOR	18 AWG (16/30) Tinned Copper
INSULATION	PE .018"
COLOR CODE	Black/White
SHIELD	Aluminum Polyester
DRAIN WIRE	20 AWG Stranded Tinned Copper
JACKET	PVC .025"
JACKET COLOR	Black Jacket
MARKING	TEMPERATURE CONTROL SYSTEM ZONE BUS / COMM A B C D E 0 1 2 3 4 5 6 7 8 9 25 pF/ft 18 AWG 2C SHIELDED CM OR AWM 2092 75C
OVERALL DIAMETER	.210" Nom.
CABLE WEIGHT	29 Lbs/Mft.
CAPACITANCE	25 pF/ft
IMPEDANCE	60 ohms
DC RESISTANCE	6.4 ohms/mft.
TEMPERATURE RATING	-40 C to 75 C / 300 Volt

INDUSTRY STANDARDS



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE · T 800.379.1191 · windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC. All rights reserved.