

PART NUMBER 1202FA-RED

UL Listed and Rated Type FPLR Multi-Conductor Non-Shielded Non-Plenum Fire Alarm



CABLE SPECIFICATIONS

DESCRIPTION	12 AWG 2 Conductor Bare Copper, Non-Shielded Non-Plenum Fire Alarm, FPLR (UL)
CONDUCTOR	12 (Solid Bare Copper)
INSULATION	PVC .010"
COLOR CODE	Black/Red
LAY LENGTH	4.5" LHL (2.67 Twists per foot)
SHIELD	N/A
DRAIN WIRE	N/A
JACKET	PVC .018"
JACKET COLOR	Red Jacket
MARKING	FIRE/LIFE SAFETY CONTROL CABLE INIT. / IND. DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 12 AWG FPLR (UL) 75C ROHS MADE IN THE USA
OVERALL DIAMETER	.238" Nom.
CABLE WEIGHT	61 Lbs/Mft.
CAPACITANCE	34 pF/Ft. Nom.
IMPEDANCE	52 Ohms
TEMPERATURE RATING	0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

AGENCY APPROVALS	NEC Article 760; FPLR (UL), RoHS Compliant, Made in the USA
------------------	---



All specifications referenced are nominal measurements unless otherwise noted.