

PART NUMBER 1202PBR-BLK

UL Listed and Rated Type CL3P Multi-Conductor Non-Shielded Plenum Cable



CABLE SPECIFICATIONS

DESCRIPTION	12 AWG 2 Conductor Bare Copper, Non-Shielded Plenum, UL Listed (UL)CL3P
CONDUCTOR	12 (19 Strand Bare Copper)
INSULATION	Low-Smoke PVC .008" Nom.
COLOR CODE	Black/Red
SHIELD	N/A
DRAIN WIRE	N/A
JACKET	Low-Smoke PVC .018" Nom.
JACKET COLOR	Black Jacket
MARKING	SMARTWIRE[™] DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 12 AWG (UL CL3P ROHS MADE IN THE USA
OVERALL DIAMETER	.250" Nom.
CABLE WEIGHT	55 Lbs/Mft.
CAPACITANCE	30 pF/Ft. Nom.
IMPEDANCE	63 Ohms
DC RESISTANCE	1.58 Ohms/mft @ 20 deg C
TEMPERATURE RATING	0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed (UL) CL3P, RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC. All rights reserved.