


# PART NUMBER 1204DB-WBT-BLK

UL Listed and Rated Type TC, PLTC, FPL or NPLF Multi-Conductor Non-Shielded Non-Plenum

■ 0275/0725 FT ● WINDY CITY WIRE ABCDE0123456789 SMARTWIRE WATER WARRIOR®



SMARTWIRE  
**GLIDE**  
TECHNOLOGY

## CABLE SPECIFICATIONS

<b>DESCRIPTION</b>	12 AWG 4 Conductor Bare Copper, Non-Shielded with Water Block Tape and overall jacket. Material suitable for underground use and indoor trays, "sunlight resistant". (Low voltage industrial process control circuits, Power-Limited circuits, Power-Limited fire alarm circuits, Power-Limited try cable PLTC)
<b>CONDUCTOR</b>	12 (19 Strand Bare Copper)
<b>INSULATION</b>	PVC with Nylon
<b>COLOR CODE</b>	Black/Red/Orange/Blue
<b>SHIELD</b>	N/A
<b>DRAIN WIRE</b>	N/A
<b>JACKET</b>	PVC .040" Nom.
<b>JACKET COLOR</b>	Black Jacket
<b>MARKING</b>	WINDY CITY WIRE A B C D E 0 1 2 3 4 5 6 7 8 9 12AWG (UL) TYPE TC-ER 600V 90C DRY 75C WET "DIR BUR" "SUN RES" PLTC, FPL OR NPLF MADE IN THE USA "SMARTWIRE WATERWARRIOR Å,Å®"
<b>OVERALL DIAMETER</b>	.401" Nom.
<b>CABLE WEIGHT</b>	131 Lbs/Mft.
<b>CAPACITANCE</b>	30 pF/Ft. Nom.
<b>IMPEDANCE</b>	62 Ohms/Mft.
<b>TEMPERATURE RATING</b>	-20 C to 105 C / 600 Volt

## INDUSTRY STANDARDS

**AGENCY APPROVALS** UL Standard 1277, UL 1424 Power limited fire alarm cables, UL 1425 Non-power limited fire alarm cables, UL 13 power limited circuit cables, NEC Articles 340, 725, 760, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.



**WINDY CITY WIRE** • T 800.379.1191 • [windycitywire.com](http://windycitywire.com)

© Windy City Wire, Cable Technology & Products, LLC.  
All rights reserved.