PART NUMBER 14-04P-WHT

UL Listed and Rated Type CL3P Multi-Conductor Non-Shielded Plenum Cable

■ 0275/0725 FT •

SMARTWIRE(TM)

DEVICE/ZONE

A B C D E 0 1 2 3 4 5 6 7 8 9





CABLE SPECIFICATIONS

DESCRIPTION 14 AWG 4 Conductor Bare Copper, Non-Shielded Plenum, UL Listed (UL) CL3P

CONDUCTOR 14 (19/27) Bare Copper INSULATION Low-Smoke PVC .008"

COLOR CODE Black/White/Red/Green

> SHIELD N/A

DRAIN WIRE N/A

> JACKET Low-Smoke PVC .018"

JACKET COLOR White Jacket

> SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 14 AWG (UL) CL3P ROHS MADE IN **MARKING**

THE USA

OVERALL DIAMETER .247" Nom

> **CABLE WEIGHT** 70 Lbs/Mft.

36 pF/Ft. Nom. CAPACITANCE

IMPEDANCE 52 Ohms

TEMPERATURE RATING O C TO 75 C / 300 Volt

INDUSTRY STANDARDS

FLAME RATING Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test

AGENCY APPROVALS NEC Article 800; UL Listed (UL) CL3P, RoHS Compliant, Made

in the USA





All specifications referenced are nominal measurements unless otherwise noted.