

PART NUMBER 1402FA-RED-ORG

UL Listed and Rated Type FPLR Multi-Conductor Non-Shielded Non-Plenum Fire Alarm

■ 0275/0725 FT ● FIRE/LIFE SAFETY CONTROL CABLE INIT/IND DEVICE/ZONE ABCDE0123456789



CABLE SPECIFICATIONS

| | |
|---------------------------|--|
| DESCRIPTION | 14 AWG 2 Conductor Bare Copper, Twisted, Non-Shielded Non-Plenum Fire Alarm, FPLR (UL) |
| CONDUCTOR | 14 (Solid Bare Copper) |
| INSULATION | PVC .010" |
| COLOR CODE | Black/Red |
| LAY LENGTH | 3.75" LHL (approx. 3.2 TPF) |
| SHIELD | N/A |
| DRAIN WIRE | N/A |
| JACKET | PVC .018" |
| JACKET COLOR | Red Jacket with Orange Stripe |
| MARKING | FIRE/LIFE SAFETY CONTROL CABLE INIT. / IND. DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 14 AWG FPLR (UL) 75C ROHS MADE IN THE USA |
| OVERALL DIAMETER | .206" Nom. |
| CABLE WEIGHT | 45 Lbs/Mft. |
| CAPACITANCE | 26 pF/Ft. Nom. |
| IMPEDANCE | 72 Ohms |
| DC RESISTANCE | 2.57 Ohms/Mft @ 20 deg. C |
| TEMPERATURE RATING | 0 C to 75 C / 300 Volt |

INDUSTRY STANDARDS

AGENCY APPROVALS NEC Article 760; FPLR (UL), RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC.
All rights reserved.