

PART NUMBER 1402FA-RED-PUR

UL Listed and Rated Type FPLR Multi-Conductor Non-Shielded Non-Plenum Fire Alarm

■ 0275/0725 FT ● FIRE/LIFE SAFETY CONTROL CABLE INIT/IND DEVICE/ZONE ABCDE0123456789



CABLE SPECIFICATIONS

DESCRIPTION	14 AWG 2 Conductor Bare Copper, Twisted, Non-Shielded Non-Plenum Fire Alarm, FPLR (UL)
CONDUCTOR	14 (Solid Bare Copper)
INSULATION	PVC .010"
COLOR CODE	Black/Red
LAY LENGTH	3.75" LHL (approx. 3.2 TPF)
SHIELD	N/A
DRAIN WIRE	N/A
JACKET	PVC .018"
JACKET COLOR	Red Jacket with Purple Stripe
MARKING	FIRE/LIFE SAFETY CONTROL CABLE INIT. / IND. DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 14 AWG FPLR (UL) 75C ROHS MADE IN THE USA
OVERALL DIAMETER	.206" Nom.
CABLE WEIGHT	45 Lbs/Mft.
CAPACITANCE	26 pF/Ft. Nom.
IMPEDANCE	72 Ohms
DC RESISTANCE	2.57 Ohms/Mft @ 20 deg. C
TEMPERATURE RATING	0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

AGENCY APPROVALS NEC Article 760; FPLR (UL), RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC.
All rights reserved.